

CONTENTS OF MI015

Probes C (AI01503-128), D (AI01504-128) & E (AI01511-128):

Probes for determination of head and neck entrapment in completely bounded openings. According to EN1176-1: 2008 Annex D.2.1.

Test template (AI01505-128):

Test template for assesment of head and neck entrapment in partially bounded and V-shaped openings. According to EN1176-1:2008 Annex D.2.2.

Test device for Toggle test (AI01506-99):

Test device for determination of entrapment of clothing. According to EN1176-1:2008 Annex D.3.

Finger rods 8 mm (AI01507-128) & 25 mm (AI01510-128):

Test probe for determination of finger entrapment. According to EN1176-1: 2008 Annex D.4

8,6 mm rod (AI01508-128):

Test probe for determination of finger entrapment in chains. According to EN1176-1: 2008.

12 mm rod (AI01509-128):

Test probe for determination of pinch and crush points on rocking equipment. According to EN1176-6: 2008 Annex C.

Spring scale (AI01513-99):

For applying force to the probes for determination of head and neck entrapment in completely bounded openings. According to EN1176-1:2008 Annex D.2.1

Ring A (AI01512-128):

Test equipment for determination of hand support and/or foot support projections on rocking equipment. According to EN1176-6:2008 Annex E.

